

# Specifications

**5610 DM**

**5610 VO**

**5610 SC3**

**5610 SCF**

**7590 DM**

**7590 VO**

**7590 SC3**

**7590 SCF**

**8910 DM**

**8910 VO**

**8910 SC3**

**8910 SCF**

	inches	mm	inches	mm	inches	mm
Max Sheet Feed	60.5 x 85"	1537 x 2159	60.5 x 115"	1537 x 2921	60.5 x 135"	1537 x 3429
Max Sheet Feed with Skip Feed	121 x 85"	3073 x 2159	121 x 115"	3073 x 2921	121 x 135"	3073 x 3429
Min Sheet Feed Manual Side Guides	18 x 26.25"	457 x 667	18 x 26.25"	457 x 667	18 x 26.25"	457 x 667
Min Sheet Feed Powered Side Guides	18 x 25.75"	457 x 654	18 x 25.75"	457 x 654	18 x 25.75"	457 x 654
Min Sheet Feed with Optional Scoring/Slitting Shafts incorporated in Diecut Section	18"	457	18"	457	18"	457
Max Print Width	79"	2007	109"	2769	129"	3277
Max Diecut Width	78"	1981	108"	2743	128"	3251
Print Cylinder Lateral Adjustment Range	1.0"	25	1.0"	25	1.0"	25
Max Nip Opening	.5625"	14	.5625"	14	.5625"	14
Diecut Cylinder Lateral Adjustment Range	1.0"	25	1.0"	25	1.0"	25
Impression Roll Diameter	7.167"	182	7.167"	182	7.167"	182
Upper Knurled Feed Roll Diameter	7.167"	182	7.167"	182	7.167"	182
Lower Rubber Feet Roll Diameter	8.053"	205	8.053"	205	8.053"	205
Anilox Roll Diameter	8.333"	212	8.333"	212	10.833"	275
Max Machine Speed	180 Blanks/Min		180 Blanks/Min		Varies	



Air - 100 psi Dry Compressed Air Required at Machine

Water - No Water Treatment Required